

Date Prepared/Revised: 5/12/2015 Version no.: 01 Supersedes: (-)

# 1.) Identification of the Mixture and of the Company

Product identifier: Copper Anti-Seize Product name: 9122 8oz Copper Anti-Seize 9123 16oz Copper Anti -Seize

Relevant identified uses of the substance: Use on threaded connections, metal fittings, packing, sleeves,

flanges, machinery, pumps, valves, manifolds, heat exchangers, compressors, bushings, and castings turbines.

Uses advised against: Do not use in oxygen service

CAS No:	Not Applicable (mixture)
EC No:	Not Applicable (mixture)
Index No:	Not Applicable (mixture)
Manufacturer/Supplier:	Aervoe Industries Incorporated
Street address/P.O. Box:	1100 Mark Circle
Country ID/Postcode/Place	Gardnerville, Nevada 89410
Telephone number:	001 (0) 1-775-782-0100
e-mail:	mailbox@aervoe.com
National contact:	Aervoe Industries Incorporated
For Product Information:	001 (0) 1-800-227-0196
Emergency telephone number:	001 (0) 1-800-424-9300 (CHEMTREC – 24 hrs)
	English Language Service

Danger

#### 2. Hazards identification

Hazards:	STOT SE 3
	STOT RE 1

# Labeling

Signal Word:

Hazard Statements:

	H335 – May cause respiratory irritation H372 – Causes damage to organs –lungs- through prolonged or repeated exposure
Precautionary Statements:	P201 – Obtain special instructions before use
	P202 – Do not handle until all safety precautions have been read and understood
	P260 – Do not breathe dust/fume/gas/mist/vapors/sprays
	P264 – Wash hands thoroughly after handling
	P270 – Do not eat, drink or smoke when using this product
	P280 – Wear protective gloves/protective clothing/eye protection
	P304+P340 – IF INHALED: remove victim to fresh air and keep at rest in
	a position comfortable for breathing

#### Date Prepared/Revised: 5/12/2015 Version no.: 01 Supersedes: (-)

P314 – Get medical attention/advice if you feel unwell. P308+P313 – IF exposed or concerned: Get medical attention/advice. P312 - Call POISON CENTER or doctor/physician if you feel unwell. P403+P233 Store container tightly in well-ventilated place. P501 – Dispose of contents and containers in accordance with local, regional, national, and international regulations.



Symbols/Pictograms:

## 3. Composition / Information on Ingredients

#### Composition

Chemical	CAS Number	Weight Percent
Aliphatic petroleum distillate	64742-52-5	40-70%
Graphite	7782-42-5	10-30%
Silica, amorphous treated	112945-52-5	1-5%
Copper	7440-50-8	10-30%

## **Other Product Information**

Chemical Identity: Mixture

## 4.) First Aid Measures

General Advice:	If symptoms persist, always call a doctor.
Inhalation First Aid:	Remove victim to fresh air and provide oxygen if breathing is
	difficult. If not breathing, give artificial respiration, preferably
	mouth to mouth. Get medical attention immediately.
Skin Contact First Aid:	Wash with soap and water. Remove contaminated clothing and
	shoes. Get medical attention immediately. Wash clothing before
	reuse.
Eye Contact First Aid:	If contact with eyes, immediately flush eyes with plenty of water
	for at least 15 minutes, while holding eyelids open. Get medical
	attention immediately.
<b>Ingestion First Aid:</b>	If swallowed, wash out mouth with water provided the person is
	conscious. Do not induce vomiting. Never give anything by mouth
	to an unconscious person. Get medical attention immediately.
Most Important	
Symptoms/Effects:	Exposure may cause slight irritation to the skin, eyes, and respiratory tract.
	Excessive exposure may cause central nervous system effects.

Date Prepared/Revised: 5/12/2015 Version no.: 01 Supersedes: (-)

## 5. Fire Fighting Measures

Flammable Properties: Auto Ignition Temperature:	Combustible paste Not Available
Suitable extinguishing media:	Carbon dioxide, dry chemical, water spray.
Unsuitable extinguishing media:	None known
Special hazards arising from the	
substance or mixture:	None known
Hazardous combustion products:	Carbon dioxide, Carbon monoxide
Fire & Explosion Hazards:	Closed Containers may rupture due to the buildup of pressure
	from extreme temperatures.
pressu NIOS	vater spray to cool containers exposed to heat or fire to prevent are build up. In the event of a fire, wear full protective clothing and H- approved self-contained breathing apparatus with full face piece and in the pressure demand or other positive pressure mode.

# 6. Accidental Release Measures

## PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
- 2) Maintain adequate ventilation.

## SPILL CLEAN-UP PROCEDURES:

- 1.) Evacuate unprotected personnel from the area.
- 2.) Remove sources of ignition if safe to do so.
- 3.) Pickup spilled materials using non-sparking tools and place in an appropriate container for disposal.
- 4.) Contain spill to prevent material from entering sewage or ground water systems.
- 5.) Always dispose of waste materials in accordance with all EU, National and Local Regulations.

### 7. Handling and Storage

### Handling:

Flammable liquid, use in a well ventilated area.

Do not use near sources of ignition.

- Do not to eat, drink and smoke while working with this material.
- Wash hands after use.

# Conditions for safe storage, including any incompatibilities:

Store out of direct sunlight. Storage Temperature: 32° to 120°F (0° to 49°C). No known incompatibilities.



Date Prepared/Revised: 5/12/2015 Version no.: 01 Supersedes: (-)

## **Appropriate engineering controls:**

Ensure adequate ventilation. A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits.

Keep away from sources of ignition.

Take precautionary measures against static discharge.

## **Personal Protection:**

Eye & face protection devices such as safety glasses, safety goggles or face shield are recommended.

### **Skin protection**

Wear the appropriate protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

### **Respiratory protection:**

Use only in an adequately ventilated area. For unknown vapor concentrations use a positive-pressure, pressure-demand, self-contained breathing apparatus (SCBA).

Hazardous Ingredient	CAS	ACGIH TLV	OSHA PEL (TWA)	
	Number	(TWA)		
Aliphatic petroleum	64742-52-5	N/AV	NA	
distillate				
Graphite	7782-42-5	2mg/m3	532.5ppm/15 mppcf	
Silica, amorphous treated	112945-52-5	N/AV	N/AV	
Copper	7440-50-8	0.2mg/m3 (fume)	0.1 (fume)	
		1 mg/m3 (dust)	0.1 (dust)	

### \*Values are based on the 2014 Guide to Occupational Exposure Values by ACGIH

## 9. Information on Basic Physical and Chemical Properties

Appearance: Copper-colored. Paste	Odor: Petroleum like
Odor Threshold: N/AV	pH: Not Applicable (solvent Base)
Melting Point: 500°F (260°C)	Freezing Point: N/AV
Initial Boiling Point: N/AV	Boiling Point Range: N/AV
Flash Point: 325°F (163°C)	Evaporation Rate: N/AV
Flammability: combustible paste	Upper LEL: N/AV Lower LEL: N/AV
Vapor Pressure: N/AV	Vapor Density: Heavier Than Air
Relative Density: N/AV	Solubility: Negligible
Partition Coefficient:	Auto-ignition Temperature: N/AV
n-octanol/ water: N/AV	
Decomposition Temperature: N/AV	Viscosity: N/AV
Explosive Properties: N/AV	Oxidizing Properties: N/AV

### **10. Stability & Reactivity**

Possibility of hazardous reactions: Hazardous polymerization will not occur under normal conditions

Date Prepared/Revised: 5/12/2015 Version no.: 01 Supersedes: (-)

Chemical stability: Stable under normal conditions Conditions to avoid: Heat and ignition sources Incompatible materials: Strong Oxidizing Agents Hazardous decomposition products: Will not occur

## **11. Toxicological Information**

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood

Routes of exposure: Eyes, skin, ingestion, and/or inhalation

Acute toxicological data: Eye irritation data:	N/AV N/AV
Skin irritation/sensitization/absorption data: Reproductive toxicity data:	N/AV N/AV
Mutagenicity data:	N/AV
Symptoms associated with physical contact:	N/AV
Acute/chronic effects from short/long term exposure:	Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis. Not expected to be a skin sensitizer.

Known reportable carcinogens via the following agencies:

NTP:	N/AV
IARC:	N/AV
OSHA:	N/AV

\* Petroleum distillates may contain chemical carcinogens in limited quantities (< 0.01%). These quantities are determined by the supplier/fraction/purity of the distillate during the manufacturing process. Chemicals that may be present within distillates are listed on California's prop 65 list such as ETHYLBENZENE, BENZENE, and TOLUENE.

#### **12. Ecological Information**

Ecotoxicity: **No Data Available** Persistence and degradability: **No Data Available** Bioaccumulative potential: **No Data Available** Mobility in soil: **No Data Available** 

Date Prepared/Revised: 5/12/2015 Version no.: 01 Supersedes: (-)

Results of PBT and vPvB assessment: **No Data Available** Other adverse effects: **No Data Available** 

## **13. Disposal Considerations**

**Waste Disposal:** Dispose of material in accordance with EU, national and local requirements. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permitted under applicable rules, regulations and/or laws governing your location.

**Product / Packaging disposal:** Dispose of packaging in accordance with federal, state and local requirements, regulations and/or laws governing your location.

## **14. Transportation Information**

#### **US DOT**

UN	Proper Shipping Name	Hazard	Packing	Marine	Special
Number		Class	Group	Pollutant	Provisions
Not	Non Regulated Material	Not	Not	NO	Reference 49
Applicable		Applicable	Applicable		CFR 172.101

#### IMDG

	-					
ſ	UN	Proper Shipping Name	Hazard Class	Packing	Marine	Special
	Number			Group	Pollutant	Provisions
ſ	UN3082	ENVIRONMENTALLY	9	PGIII	YES	Reference
		HAZARDOUS				IMDG code
		SUBSTANCE, LIQUID,				part 3
		N.O.S., (COPPER)				_

#### IATA:

UN	Proper Shipping Name	Hazard Class	Packing	Marine	Special
Number			Group	Pollutant	Provisions
Not	Non Regulated Material	Not	Not	Not	Reference
Applicable		Applicable	Applicable	Applicable	IATA
					Dangerous
					Goods
					Regulation

### **15. Regulatory Information**

### Workplace classification:

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). The Occupational Safety and Health Administration's interpretation of the product's hazard to workers.

# SARA Title 3:

Section 311/312 Categorizations (40 CFR 372): This product is a hazardous chemical under 29 CFR 1910.1200, and is categorized as an immediate and delayed health, and flammability physical hazard. Superfund Amendment and Reauthorization Act (SARA) category. SARA requires reporting any spill of any hazardous substance.

**TSCA status:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.



Date Prepared/Revised: 5/12/2015 Version no.: 01 Supersedes: (-)

**WHMIS:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the (M)SDS contains all of the information required by the CPR. **PROP 65 (CA):** WARNING: This product may contain chemicals know to the state of California to cause cancer, birth defects or other reproductive harm.

## **16. Other Information**

This SDS has been completed in accordance with GHS Rev04 (2011): U.S OSHA, CMA, ANSI, Canadian WHMIS standards, and European Directives.

Date of Preparation/Revision: 5/12/2015 Supersedes: (-)

To the best of our knowledge, the information contained herein is believed to be accurate. However, the above data does not imply any guarantee or warranty of any kind, expressed or implied. The final determination of the suitability of any material is the sole responsibility of the user. All materials made present un-known hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards existing.