

## DRILLING & TAPPING FLUIDS & LUBRICANTS

## **Increase Productivity and Extend Tool Life**

- For tapping and drilling stainless steel, carbon steel, inconel, monel, hastelloy, titanium, aluminum and other alloys and exotics
- Improve Finish and Size Accuracy
- Does not contain 1,1,1 Trichloroethane

**Drilling and Tapping Fluid** - A heavy oil that sticks to the tool throughout extreme operations and reduces torque. It is environmentally safe and has a mild but pleasant odor.

**Light** - A light viscosity heavy duty drilling and tapping fluid that reduces torque. It is ideal in a re-circulating system and can be added to cutting oils to increase E.P. and lubricity properties. It will not contaminate the coolant in the machine sump and floats to the surface for easy skimming.

**Foamy** - A heavy duty aerosol that foams on contact to coat the cutting tool. It is ideal for use on a mill or lathe and will not contaminate the coolant.

Wax Stick - Multi-purpose lubricant which effectively removes heat and lubricates while withstanding tremendous pressures. It may be used as a replacement for tapping fluids and cutting oils and is ideal for metal sawing, drilling, tapping, pipe threading and as a cement form releasing agent.



Size	Style	Description	Pkg qty	EDP#
1/2 oz	Trial size	Drilling & Tapping Fluid	1	1910512
4 oz	Squirt Bottle	Drilling & Tapping Fluid	24	1910501
16 oz	Squirt Bottle	Drilling & Tapping Fluid	12	1930502
16 oz	Squirt Bottle	Drilling & Tapping Fluid	1	46437348
1 gal	Bottle	Drilling & Tapping Fluid	6	1930503
5 gal	Dispenser	Drilling & Tapping Fluid	1	1910506
5 gal	Pail	Drilling & Tapping Fluid	1	1910504
55 gal	Drum	Drilling & Tapping Fluid	1	1910505
16 oz	Squirt Bottle	Light Tapping Fluid	1	46437347
16 oz	Squirt Bottle	Light Tapping Fluid	12	1910502
1 gal	Squirt Bottle	Light Tapping Fluid	6	1910503
20 oz	Aerosal Can	Foam	1	46437349
20 oz	Aerosal Can	Foam	12	1910509
1 lb	Stick	Wax	1	46437430
1 lb	Stick	Wax	24	1950501

